

Product Code:

824-1715	Black
824-1716	Brown
824-1718	Natural
824-1719	Bronze
824-1721	Walnut
824-1722	White

VISCOSITY:	N/A
FLASH POINT:	N/A
DENSITY (lb/gal):	8.29 – 9.51
SOLID (% by weight):	15.5% - 32.7%
SOLID (% by volume):	6.4% - 12.1%
SHELF LIFE (months):	12

Product Description: BA Glaze 824-17XX is an all-purpose break-away glaze for furniture and cabinets.

Uses: BA Glaze is used for coloring of wood and is especially developed for furniture coating systems. BA Glaze is recommended for indoor use.

Environmental Data (as supplied):

VOC less exempt lb/gal:	<2.7
VOC lb/gal:	<0.45
VOC less exempt g/l:	<320
VOC g/l:	<55
VOC lb/lb Solid:	<0.16
VHAPs lb/lb Solid:	<0.00

See individual compliance sheets for specific data

Application Data:

SUGGESTED USES:	Wood Glaze
MIXING RATIO:	N/A
POT LIFE:	N/A
APPLICATION VISCOSITY:	N/A
REDUCER:	N/A
RETARDER:	N/A
CLEAN-UP SOLVENT:	800-5500
RECOMMENDED WET FILM:	N/A

Directions for Use

Surface Preparation: N/A

General Information: Apply the BA Glaze by spraying. Allow to dry and then brush off.

BA Glaze must be thoroughly agitated to ensure product consistency.

The completed coating system should be checked for required properties prior to start-up of production.

IMPORTANT: Product must be thoroughly agitated before use.

THE CUSTOMER IS RESPONSIBLE FOR FOLLOWING THE RECOMMENDED APPLICATION PROCEDURES. FAILURE TO ADHERE TO THE RECOMMENDATIONS GIVEN IN THIS DATA SHEET WILL LIKELY RESULT IN UNSATISFACTORY FILM APPEARANCE OR FILM FAILURE. THE COMPLETE COATING SYSTEM SHOULD BE CHECKED FOR REQUIRED PROPERTIES PRIOR TO THE START-UP OF PRODUCTION.

Drying Times: Let dry until BA glaze can be brushed off cleanly.

Note: Dry times are greatly affected by film build, porosity of substrate, air movement as well as heat and humidity. Temperatures are based on actual board temperature. This may vary depending on length of time for boards to reach these temperatures. Minimum curing temperatures of 64°F/18°C must be maintained throughout the curing cycle to achieve the film integrity as stated in product features.

These products are designed for industrial use only. AkzoNobel views safety as a top priority. Please refer to Material Safety Data Sheet for information on the safe use of this product.

Values shown are calculated estimates and should not be construed as product specifications. We cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and users assume all responsibility and liability for loss or damage arising from the use of our products whether used alone or a combination with other products. Use of unapproved or reclaimed solvent blends may reduce film properties and is not recommended.

Akzo Nobel Coatings, Inc.
1431 Progress Ave
High Point, NC 27260
336-841-5111