



Chemcraft®

A Great Finish is Only the Beginning

Promatch® Aqua Mono Color WB Stain
824-50XX

Product Codes:

824-5001 Yellow G	824-5006 White
824-5002 Yellow R	824-5007 Blue
824-5003 Red Y	824-5008 Green
824-5004 Orange	824-5009 Red B
824-5005 Black	824-5010 Magenta

VISCOSITY:	N/A
FLASH POINT:	55° F
DENSITY (lb/gal):	6.84 to 6.92
SOLID (% by weight):	8.8 to 11.6%
SOLID (% by volume):	6.9 to 9.2%
SHELF LIFE (months):	12

Product Description: Nanotechnology comes to the world of color. A complete line of waterborne stains that can be intermixed to achieve any type of color desired. This versatile group is designed for spray applications, but can be easily modified to allow for wiping using the wipe 20 solution. Ten stock colors can be used right out of the package, or intermixed to create a full color pallet.

Uses: Unlimited uses. It was designed as a stain color system for the ora Verde urethane system. This one doesn't stop there. You can use these colors under acid catalyzed systems as well as any other Chemcraft brand of coatings.

Environmental Data (as supplied):

VOC less exempt lb/gal:	<4.95
VOC lb/gal:	<1.0
VOC less exempt g/l:	<591
VOC g/l:	<118
VOC lb/lb Solid:	<1.95
VHAPs lb/lb Solid:	<0.10

Application Data:

SUGGESTED USES:	Promatch Aqua color stain system.
MIXING RATIO:	N/A
POT LIFE:	N/A
APPLICATION VISCOSITY:	N/A
REDUCER:	N/A
RETARDER:	N/A
CLEAN-UP SOLVENT:	N/A
RECOMMENDED WET FILM:	N/A

Directions for Use

Promatch® Aqua Mono Color WB Stain
824-50XX

Surface Preparation: Substrate must be sanded using 120, 150 or 180 grit paper prior to staining.

THE CUSTOMER IS RESPONSIBLE FOR FOLLOWING THE RECOMMENDED APPLICATION PROCEDURES. FAILURE TO ADHERE TO THE RECOMMENDATIONS GIVEN IN THIS DATA SHEET WILL LIKELY RESULT IN UNSATISFACTORY FILM APPEARANCE OR FILM FAILURE. THE COMPLETE COATING SYSTEM SHOULD BE CHECKED FOR REQUIRED PROPERTIES PRIOR THE START-UP OF PRODUCTION.

Drying Times:

	Room Temperature (68°F)	Forced Drying Schedule (122°F)
Tack Free Time:	N/A	N/A
Dry to Sand:	N/A	N/A
Dry to Stack:	N/A	N/A

Recommended time before applying sealer: 20 – 30 minutes.

Note: Dry times are greatly affected by film build, porosity of substrate, air movement as well as heat and humidity. Temperatures are based on actual board temperature. This may vary depending on length of time for boards to reach these temperatures. Minimum curing temperatures of 64° F/18° C must be maintained throughout the curing cycle to achieve the film integrity as stated in product features

These products are designed for industrial use only. AkzoNobel views safety as a top priority. Please refer to Material Safety Data Sheet for information on the safe use of this product.

Values shown are calculated estimates and should not be construed as product specifications. We cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and users assume all responsibility and liability for loss or damage arising from the use of our products whether used alone or a combination with other products. Use of unapproved or reclaimed solvent blends may reduce film properties and is not recommended.

Akzo Nobel Coatings, Inc
1431 Progress Ave
High Point, NC 27260
336-841-5111